

XTV 12950

12 95


XTV 12950 -



: 12 (-20° +50°).
400 -
100%

-	6											
	12											
	95 A	10-				U	- 1.80 /		25°			
		32.8										
	800A (5)											
	6.5											
		: -20° +50° ;				: -20° +50° ;						
	25°											
	13.5 - 13.8	25°										
	28.5 A (I _{max}
	14.4 - 15.0	25°										
	6	25°										*
	6											

*



: A (25°)												
U _k /T	5	10	15	30	1	2	3	4	5	8	10	20
1.60 /	361	250	191	116	69.2	41.1	28.3	21.6	17.9	11.9	10.0	5.18
1.67 /	319	233	182	114	67.8	40.2	28.0	21.5	17.7	11.8	9.79	5.15
1.70 /	298	223	177	112	67.0	39.9	27.6	21.4	17.6	11.7	9.72	5.13
1.75 /	264	206	169	107	65.1	38.7	26.9	21.0	17.4	11.6	9.59	5.07
1.80 /	240	186	156	101	62.7	37.0	26.4	20.7	17.0	11.4	9.50	4.98
1.85 /	198	166	136	92.4	58.5	34.7	25.0	19.5	16.3	11.0	9.05	4.79

: / (25°)												
U _k /T	5	10	15	30	1	2	3	4	5	8	10	20
1.60 /	3,383	2,525	2,032	1,258	768	457	324	254	209	140	117	60.7
1.67 /	3,128	2,400	1,972	1,244	757	451	321	250	207	139	116	60.0
1.70 /	3,021	2,330	1,950	1,232	755	448	318	249	206	138	115	59.7
1.75 /	2,833	2,186	1,829	1,193	739	437	310	245	204	136	114	59.4
1.80 /	2,496	2,029	1,675	1,137	713	419	304	238	198	134	113	58.5
1.85 /	2,124	1,804	1,476	1,056	672	398	289	226	189	129	108	56.8