

SPC T26 15 D



Product description: SPC T26 15 D Product code: 4008321965004

Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog: http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321965004

Applications				
Dimmable		No		
Certificates & Standard	ls			
EEI - Energy Label		A		
General Description		Olympia		
Design / version	-t:\	Clear		
Base (standard designa	ation)	E14 Yes		
Mercury-free				
Recycling		Yes		
New article		NEW		
Technical - Electrical D	ata			
Nominal wattage	***	0.8 W		
Rated wattage		0.8 W		
Nominal voltage (produ	ict)	220-240 V		
Operating frequency	iot,	5060 Hz		
operating nequency		0000112		
Technical - Geometries	3			
Overall length		61.00 mm		
Diameter		26.0 mm		
Length [PICOS]		61 mm		
Technical - Lifespan				
Nominal lamp life time		10000 h		
Rated lamp life time		10000 h		
Lifespan		10000 h		
Technical - Light Techn	nical Data			
Rated color rendering index (Ra)		65		
Luminous flux		65 lm		
Nominal luminous flux		65 lm		
Rated luminous flux		65 lm		
Color temperature		6500 K		
Color rendering index Ra		70		
Light color as per EN 12464-1		Daylight		
Rated starting time		0 s		
Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume

Packaging units							
Product code	Packaging type and content	Dimensions in h x w x I	Gross weight	Volume			
4008321965004	Folding carton box contains 1 Piece	28,000 mm x 28,000 mm x 64,000 mm	16,000 g (0,000 g)	0,050 Cubic dec.			



SPC T26 15 D

Packaging units								
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume				
4008321965011	Shipping carton box contains 20 Piece	120,000 mm x 77,000 mm x 150,000 mm	360,000 g (0,000 g)	1,386 Cubic dec.				

PARATHOM SPECIAL T26 with its Daylight color is ideal for use in refrigerators or sewing machines.

- Very low energy consumption
 Long life
 Shockproof and vibration-proof
 Extremely small dimensions
 Suitable for use indoors or outdoors
 Not suitable for use with dimmers