LP SERIES-General Purpose

LP12-6.0 (12V6.0AH)

Specification

Nomial Voltage	12V	
Nomial Capacity(20HR)	6.0AH	
Dimension	Length	90±1mm (3.54 inches)
	Width	70±1mm (2.76 inches)
	Container Height	101±1mm (3.98 inches)
	Total Height (with Terminal)	107±1mm (4.21 inches)
Approx Weight	Approx 1.8 kg (3.97lbs)	
Terminal	T1 / T2	
Container Material	ABS	
Rated Capacity	6.00 AH/0.30A	(20hr ,1.80V/cell,25°C/77°F)
	5.58 AH/0.558A	(10hr,1.80V/cell,25°C/77°F)
	5.10 AH/1.02A	(5hr,1.75V/cell,25°C/77°F)
	4.59 AH/1.53A	(3hr,1.75V/cell,25°C/77°F)
	3.77 AH/3.77A	(1hr,1.60V/cell,25°C/77°F)
Max. Discharge Current	90A (5s)	
Internal Resistance	Approx 25mΩ	
Operating Temp.Range	Discharge : -15～50°C (5～122°F)	
	Charge : 0～40°C (32～104°F)	
	Storage : -15～40°C (5～104°F)	
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than1.8A.Voltage 14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage 13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	Leoch LP series batterys may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Applications

- *All purpose*
- *Uninterruptable Power Supply (UPS)*
- *Electric Power System (EPS)*
- *Emergency backup power supply*
- *Emergency light*
- *Railway signal*
- *Aircraft signal*
- *Alarm and security system*
- *Electronic apparatus and equipment*
- *Communication power supply*
- *DC power supply*
- *Auto control system*

VdS | Intertek ETL SEMKO | MH26866 | ISO14001 | ISO9001 | CE EMC tested

Constant Current Discharge (Amperes) at 25 °C (77°F)


F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	11.4	8.77	7.27	6.28	4.86	3.58	3.02	1.78	1.40	1.14	0.93	0.80	0.648	0.541	0.297
1.80V/cell	15.3	11.2	8.78	7.43	5.73	4.16	3.38	1.95	1.50	1.21	0.99	0.86	0.687	0.558	0.300
1.75V/cell	17.3	12.3	9.59	7.99	5.95	4.32	3.54	2.02	1.53	1.24	1.02	0.89	0.699	0.573	0.303
1.70V/cell	19.0	13.4	10.2	8.40	6.20	4.49	3.65	2.07	1.57	1.27	1.05	0.90	0.709	0.584	0.308
1.65V/cell	21.0	14.5	10.9	8.92	6.54	4.61	3.73	2.10	1.64	1.32	1.07	0.92	0.720	0.596	0.313
1.60V/cell	23.2	15.7	11.6	9.50	6.90	4.80	3.77	2.19	1.69	1.36	1.11	0.94	0.727	0.603	0.314


Constant Power Discharge (Watts) at 25 °C (77°F)


F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	20.9	16.2	13.6	11.8	9.26	6.88	5.82	3.47	2.72	2.22	1.82	1.58	1.279	1.071	0.588
1.80V/cell	27.7	20.5	16.2	13.8	10.8	7.94	6.48	3.76	2.91	2.36	1.94	1.69	1.353	1.103	0.593
1.75V/cell	30.6	22.1	17.4	14.7	11.1	8.16	6.75	3.88	2.95	2.40	1.98	1.73	1.373	1.131	0.599
1.70V/cell	32.8	23.6	18.4	15.3	11.5	8.46	6.94	3.97	3.03	2.46	2.03	1.76	1.391	1.153	0.609
1.65V/cell	35.6	25.2	19.4	16.2	12.0	8.59	7.05	4.00	3.15	2.54	2.08	1.79	1.409	1.174	0.616
1.60V/cell	38.4	26.7	20.4	17.0	12.6	8.90	7.08	4.16	3.23	2.61	2.14	1.83	1.420	1.185	0.619

Dimensions


T1 Terminal
Unit: mm [inches]









Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics



A No supplementary charge required
(Carry out supplementary charge before use if 100% capacity is required.)

B Supplementary charge required before use.Optional charging way as below:
1.Charged for above 3 days at limted current 0.25CA and constant volatge 2.25V/cell.
2.Charged for above 20hours at limted current 0.25CA and constant volatge 2.45V/cell.
3.Charged for 8~10hours at limted current 0.05CA .

C Supplementary charge may often fail to recover the capacity.
The battery should never be left standing till this is reached.

Sales Office

China sales office:
Add:5th Floor,Xinbaohui Bldg.,Nanhai Blvd.,
Nanshan,Shenzhen, China. 518052
Tel:+ 86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail:export@leoch.com
Http://www.leoch.com

North America sales office:
Add: 19751 Descartes, Unit A,
Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us
Http://www.leoch.us

Europe sales office:
Add: LaCampagna House. Main Road.
Gloucester. GL2-8JH. United Kingdom
Tel: +44(0) 1452 751016
E-mail: Sales.Europe@leoch.com
Http://www.leoch.com