LP SERIES-General Purpose

LP12-65 (12V65AH)

Specification

Nomial Voltage	12V	
Nomial Capacity(10HR)	65.0AH	
Dimension	Length	348±3mm (13.70 inches)
	Width	167±2mm (6.57 inches)
	Container Height	178±2mm (7.01 inches)
	Total Height (with Terminal)	178±2mm (7.01 inches)
Approx Weight	Approx 19.2 kg (42.3lbs)	
Terminal	T6 / T10	
Container Material	ABS	
Rated Capacity	67.6 AH/3.38A	(20hr ,1.80V/cell,25°C/77°F)
	65.0 AH/6.50A	(10hr,1.80V/cell,25°C/77°F)
	56.0 AH/11.2A	(5hr,1.75V/cell,25°C/77°F)
	50.7 AH/16.9A	(3hr,1.75V/cell,25°C/77°F)
	39.7 AH/39.7A	(1hr,1.60V/cell,25°C/77°F)
Max. Discharge Current	780A (5s)	
Internal Resistance	Approx 7.3mΩ	
Operating Temp.Range	Discharge : -15～50°C (5～122°F)	
	Charge : 0～40°C (32～104°F)	
	Storage : -15～40°C (5～104°F)	
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than 19.5A.Voltage 14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage 13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	Leoch LP series batterys may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Applications

- *All purpose*
- *Uninterruptable Power Supply (UPS)*
- *Electric Power System (EPS)*
- *Emergency backup power supply*
- *Emergency light*
- *Railway signal*
- *Aircraft signal*
- *Alarm and security system*
- *Electronic apparatus and equipment*
- *Communication power supply*
- *DC power supply*
- *Auto control system*

Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	111.2	87.5	74.4	62.2	49.4	37.4	30.6	19.5	15.4	12.6	10.2	8.85	7.18	6.14	3.35
1.80V/cell	149.3	111.8	89.9	73.5	58.3	43.5	34.3	21.3	16.6	13.5	10.9	9.49	7.62	6.50	3.38
1.75V/cell	168.4	122.8	98.2	79.1	60.6	45.2	35.9	22.1	16.9	13.8	11.2	9.75	7.75	6.57	3.41
1.70V/cell	185.4	133.8	104.8	83.1	63.0	47.0	37.0	23.0	17.4	14.1	11.5	9.95	7.86	6.63	3.48
1.65V/cell	204.5	144.4	111.4	88.3	66.5	48.1	38.3	23.6	18.1	14.6	11.8	10.2	7.98	6.77	3.52
1.60V/cell	225.5	156.8	119.2	94.1	70.2	50.2	39.7	24.4	18.7	15.1	12.2	10.4	8.06	6.84	3.54


Constant Power Discharge (Watts) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	203.4	161.6	138.8	117.3	94.2	71.9	59.1	37.9	30.1	24.6	19.9	17.4	14.2	12.1	6.63
1.80V/cell	270.1	204.0	165.4	136.6	109.5	83.0	65.9	41.1	32.2	26.2	21.3	18.6	15.0	12.8	6.69
1.75V/cell	298.1	220.6	178.5	145.5	112.7	85.3	68.6	42.5	32.7	26.7	21.8	19.0	15.2	13.0	6.74
1.70V/cell	319.1	235.0	187.9	151.8	116.7	88.4	70.5	44.1	33.5	27.3	22.3	19.4	15.4	13.1	6.87
1.65V/cell	346.9	251.2	198.3	160.1	122.1	89.8	72.4	45.0	34.8	28.2	22.8	19.8	15.6	13.3	6.95
1.60V/cell	373.8	266.5	208.5	168.6	128.0	93.1	74.5	46.3	35.7	28.9	23.5	20.1	15.7	13.4	6.98


Dimensions

T6 Terminal


Unit: mm [inches]




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics



A No supplementary charge required
(Carry out supplementary charge before use if 100% capacity is required.)

B Supplementary charge required before use.Optional charging way as below:
1.Charged for above 3 days at limted current 0.25CA and constant volatge 2.25V/cell.
2.Charged for above 20hours at limted current 0.25CA and constant volatge 2.45V/cell.
3.Charged for 8~10hours at limted current 0.05CA .

C Supplementary charge may often fail to recover the capacity.
The battery should never be left standing till this is reached.

Sales Office

China sales office:

Add:5th Floor,Xinbaohui Bldg.,Nanhai Blvd.,
Nanshan,Shenzhen, China. 518052
Tel:+ 86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail:export@leoch.com
Http://www.leoch.com

North America sales office:

Add: 19751 Descartes, Unit A,
Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us
Http://www.leoch.us

Europe sales office:

Add: LaCampagna House. Main Road.
Gloucester. GL2-8JH. United Kingdom
Tel: +44(0) 1452 751016
E-mail: Sales.Europe@leoch.com
Http://www.leoch.com