





## EBX7L-BS [12V6Ah]



### Dimensions (mm)




### Standard Terminal (mm)



### Physical Specification

Nominal Voltage		12V
Nominal Capacity (10HR)		6AH
Dimension	Length	113 ±2mm (4.45 inches)
	Width	70 ±2mm (2.76 inches)
	Container Height	130 ±2mm (5.12 inches)
	Total Height (with Terminal)	130 ±2mm (5.12 inches)
Weight	Battery(with acid): Approx 2.40kg (5.29lbs)	
	Electrolyte: Approx 0.45kg (0.99lbs)	
* Sealed and non-spillable AGM battery		
* Maintenance-free		
* Powerful 85 cold cranking amps		
* Shipped pre-charged and ready to install		
* Replaces / upgrade for EB7-3		

### Discharge Characteristics (25°C, 77°F)



### Electrical Specification

Rated Capacity	10 hour rate (0.60 A)	6.00AH
	5 hour rate (0.98 A)	4.92AH
	2 hour rate (2.10 A)	4.20AH
	1 hour rate (3.60 A)	3.60AH
	0.5 hour rate (6.48 A)	3.24AH
Capacity affected by Temperature	40 °C (104 °F)	106%
	25 °C (77 °F)	100%
	0 °C (32 °F)	86%
	-15 °C (5 °F)	65%
Self Discharge	Approximately 3% per month (25°C (77°F))	
Charging Methods	Full Charge	Constant-Voltage Charge: Initial charging current: less than 1.8A Voltage: 14.40 V ~ 15.00 V at 25 °C (77 °F) Charging time: 15 ~18h Constant-Current Charge: Charging current: 0.1C <sub>10</sub> =0.60A, when charging voltage up to 14.40V, continue to charge 4h
	Floating Charge	No limit on Initial charging current Voltage: 13.50 V ~ 13.80 V at 25 °C (77 °F)