



product details

CL P 25 FR D

Product description: CL P 25 FR D
 Product code: 4008321965202
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321965202

Applications	
Dimmable	No

Categorizations	
SEG number	8333933

Certificates & Standards	
EEl - Energy Label	A

General Description	
Design / version	Frosted
Base (standard designation)	E27
Mercury-free	Yes
Lamp mercury content	0.0 mg
Recycling	Yes

Technical - Electrical Data	
Nominal wattage	4.2 W
Rated wattage	4.2 W
Claimed equivalent incand. lamp power	25 W
Nominal voltage (product)	100-240 V
Operating frequency	50...60 Hz
Rated number of switching cycles	100000
Rated power factor λ	0.50

Technical - Geometries	
Overall length	78.00 mm
Diameter	45 mm
Length	78 mm

Technical - Lifespan	
Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Lifespan	25000 h

Technical - Light Technical Data	
Rated color rendering index (Ra)	80
Luminous flux	230 lm
Nominal luminous flux	250 lm
Rated luminous flux	250 lm
Lumen main.fact.at end of nom.life time	0.70
Color temperature	6500 K
Rated color temperature	6500 K





Technical - Light Technical Data	
Color rendering index Ra	75
Light color as per EN 12464-1	Daylight
Rated warm-up time (60 %)	0 s
Rated starting time	0.0 s

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4008321965202	Folding carton box contains 1 Piece	47,000 mm x 47,000 mm x 85,000 mm	95,000 g (0,000 g)	0,188 Cubic dec.
4008321965219	Shipping carton box contains 10 Piece	106,000 mm x 115,000 mm x 248,000 mm	895,000 g (0,000 g)	2,918 Cubic dec.

PARATHOM CLASSIC P lamps provide pleasant contemporary light in no time at all. Thanks to the E27 base, the LED lamps with their warm white or cold white light can be used almost anywhere - as simple direct replacements for standard incandescent lamps.

- LED lamp for line voltage
- Very low energy consumption
- Low thermal output with no UV
- Shockproof and vibration-proof thanks to plastic casing
- Suitable for indoors and outdoors
- Instant full output, no delay

Application

- General illumination
- Decorative indoor and outdoor lighting