



product details

CL P 15 CL CW

Product description: CL P 15 CL CW
 Product code: 4008321929297
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321929297

Applications	
Dimmable	No

Categorizations	
SEG number	8333918

Certificates & Standards	
EEI - Energy Label	A

General Description	
Design / version	Clear
Base (standard designation)	E27
Mercury-free	Yes
Lamp mercury content	0.0 mg
Recycling	Yes

Technical - Electrical Data	
Nominal wattage	1.6 W
Rated wattage	1.6 W
Nominal voltage (product)	100-240 V
Operating frequency	50...60 Hz
Rated number of switching cycles	50000
Rated power factor λ	0.40

Technical - Geometries	
Overall length	90.00 mm
Diameter	45 mm
Length	90 mm

Technical - Lifespan	
Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Lifespan	25000 h

Technical - Light Technical Data	
Rated color rendering index (Ra)	70
Luminous flux	63 lm
Nominal luminous flux	63 lm
Rated luminous flux	63 lm
Lumen main.fact.at end of nom.life time	0.50
Color temperature	5500 K
Rated color temperature	5500 K
Color rendering index Ra	70



04.02.2011

Subject to change without notice. Errors and omission excepted.
 © 2010 OSRAM GmbH

Page 1 of 2

**Technical - Light Technical Data**

Light color as per EN 12464-1	Cool White
Rated warm-up time (60 %)	0 s
Rated starting time	0.0 s

Packaging units

Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4008321929297	Folding carton box contains 1 Piece	46,000 mm x 46,000 mm x 104,000 mm	78,333 g (0,000 g)	0,199 Cubic dec.
4008321929303	Shipping carton box contains 10 Piece	155,000 mm x 117,000 mm x 202,000 mm	616,000 g (0,000 g)	3,033 Cubic dec.

PARATHOM CLASSIC P lamps provide pleasant contemporary light in no time at all. Thanks to the E27 base, the LED lamps with their warm white or cold white light can be used almost anywhere - as simple direct replacements for standard incandescent lamps.

- LED lamp for line voltage
- Very low energy consumption
- Low thermal output with no UV
- Shockproof and vibration-proof thanks to plastic casing
- Suitable for indoors and outdoors
- Instant full output, no delay

Application

- General illumination
- Decorative indoor and outdoor lighting