

G95 40 FR WW



Product description: G95 40 FR WW Product code: 4008321965387

Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog: http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321965387

Applications	
Dimmable	No
Certificates & Standards	
EEI - Energy Label	A
General Description	
Design / version	Frosted
Base (standard designation)	E27
Mercury-free	Yes
Lamp mercury content	0.0 mg
Recycling	Yes
New article	NEW
Technical - Electrical Data	
Nominal wattage	10.5 W
Rated wattage	10.5 W
Claimed equivalent incand. lamp power	38 W
Nominal voltage (product)	220-240 V
Operating frequency	5060 Hz
Rated number of switching cycles	50000
Rated power factor λ	0.50
Technical - Geometries	
Overall length	130.00 mm
Diameter	95 mm
Length	130 mm
Technical - Lifespan	
Nominal lamp life time	25000 h
Rated lamp life time	25000 h
	25000 h
Lifespan	23000 11
Technical - Light Technical Data	
Rated color rendering index (Ra)	80
Luminous flux	500 lm
Nominal luminous flux	500 lm
Rated luminous flux	500 lm
Lumen main.fact.at end of nom.life time	0.70
Color temperature	3000 K
Rated color temperature	3000 K
Light color as per EN 12464-1	Warm White
Rated warm-up time (60 %)	0 s

Page 1 of 2



G95 40 FR WW

Technical - Light Technical Data	
Rated starting time	0.0 s

Packaging units						
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume		
4008321965387	Folding carton box contains 1 Piece	109,000 mm x 109,000 mm x 159,000 mm	396,300 g (0,000 g)	1,889 Cubic dec.		
4008321965394	Shipping carton box contains 6 Piece	228,000 mm x 178,000 mm x 338,000 mm	2.717,800 g (0,000 g)	13,717 Cubic dec.		

PARATHOM GLOBE lamps provide pleasant contemporary light in no time at all. Thanks to the E27 base, the LED lamps with their warm white or cold white light can be used almost anywhere - as simple direct replacements for standard incandescent lamps up to 15 W.

- LED lamp for line voltage
 Very low energy consumption
 Extremely long life
 Low thermal output with no UV
 Shockproof and vibration-proof thanks to plastic casing
 Suitable for indoors and outdoors
 Instant full output, no delay

Application

- General illumination
 Decorative indoor and outdoor lighting