



product details

**MR16 20 WW**

Product description: MR16 20 WW  
 Product code: 4008321963802  
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:  
[http://catalog.myosram.com?~language=EN&~country=COM&it\\_p=4008321963802](http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321963802)

Applications	
Dimmable	No

General Description	
Base (standard designation)	GU5.3
Mercury-free	Yes
Recycling	Yes
New article	NEW

Technical - Electrical Data	
Nominal wattage	5.5 W
Rated wattage	5.5 W
Nominal voltage (product)	12 V
Operating frequency	50...60 Hz

Technical - Geometries	
Overall length	48.50 mm
Diameter	51.0 mm
Length	51.50 mm

Technical - Lifespan	
Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Lifespan	25000 h

Technical - Light Technical Data	
Rated color rendering index (Ra)	80
Luminous intensity	450 cd
Beam angle	36 °
Color temperature	3000 K
Rated color temperature	3000 K
Color rendering index Ra	80
Light color as per EN 12464-1	Warm White
Rated starting time	0 s

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4008321963802	Folding carton box contains 1 Piece	52,000 mm x 52,000 mm x 53,000 mm	61,300 g (0,000 g)	0,143 Cubic dec.
4008321963819	Shipping carton box contains 10 Piece	273,000 mm x 71,000 mm x 113,000 mm	690,000 g (0,000 g)	2,190 Cubic dec.



07.02.2011

Subject to change without notice. Errors and omission excepted.  
 © 2010 OSRAM GmbH

Page 1 of 2



product details

## MR16 20 WW

Powerful PARATHOM PAR16 20 is ideal for economical spotlighting and can be used as an alternative to a 20 W line-voltage halogen lamp.

- Professional LED lamp for line voltage
- Very low energy consumption
- Extremely long life
- Equipped with successful OSRAM High-Power Golden DRAGON LEDs
- No UV radiation in the light beam
- Shockproof and vibration-proof thanks to LED technology
- Efficient generation of white light
- Professional thermal management

### Application

- Spotlighting for accents
- In display cabinets and shop windows
- Retail outlets and exhibition rooms
- For spotlighting heat-sensitive objects such as food, plants, etc.