



Product description: PAR16 35 25° D
 Product code: 4008321980083
 Quantity: Blister (BLI) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321980083

Applications	
Dimmable	No

General Description	
Base (standard designation)	E27
Mercury-free	Yes
Recycling	Yes

Technical - Electrical Data	
Nominal wattage	4.5 W
Rated wattage	4.5 W
Nominal voltage (product)	220-240 V
Operating frequency	50...60 Hz

Technical - Geometries	
Overall length	68.00 mm
Diameter	50 mm
Length	68 mm

Technical - Lifespan	
Nominal lamp life time	35000 h
Rated lamp life time	35000 h
Lifespan	35000 h

Technical - Light Technical Data	
Luminous intensity	950 cd
Beam angle	25 °
Color temperature	6500 K
Rated color temperature	6500 K
Color rendering index Ra	70
Light color as per EN 12464-1	Daylight
Rated starting time	0 s

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4008321980083	Blister contains 1 Piece	79,000 mm x 59,000 mm x 140,000 mm	85,000 g (0,000 g)	0,653 Cubic dec.
4008321980090	Shipping carton box contains 6 Piece	158,000 mm x 136,000 mm x 312,000 mm	664,000 g (0,000 g)	6,704 Cubic dec.



product details

PAR16 35 25° D

Powerful PARATHOM PAR16 20 is ideal for economical spotlighting and can be used as an alternative to a 20 W line-voltage halogen lamp.

- Professional LED lamp for line voltage
- Very low energy consumption
- Extremely long life
- Equipped with successful OSRAM High-Power Golden DRAGON LEDs
- No UV radiation in the light beam
- Shockproof and vibration-proof thanks to LED technology
- Efficient generation of white light
- Professional thermal management

Application

- Spotlighting for accents
- In display cabinets and shop windows
- Retail outlets and exhibition rooms
- For spotlighting heat-sensitive objects such as food, plants, etc.