



Product description: MR16 20 D
 Product code: 4008321963840
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321963840

Applications	
Dimmable	Yes

General Description	
Base (standard designation)	GU5.3
Mercury-free	Yes
Recycling	Yes
New article	NEW

Technical - Electrical Data	
Nominal wattage	5.5 W
Rated wattage	5.5 W
Nominal voltage (product)	12 V
Operating frequency	50...60 Hz

Technical - Geometries	
Overall length	48.50 mm
Diameter	51.0 mm
Length	51.50 mm

Technical - Lifespan	
Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Lifespan	25000 h

Technical - Light Technical Data	
Rated color rendering index (Ra)	80
Beam angle	36 °
Color temperature	6500 K
Rated color temperature	6500 K
Color rendering index Ra	80
Light color as per EN 12464-1	Daylight
Rated starting time	0 s

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4008321963840	Folding carton box contains 1 Piece	0,000 mm x 0,000 mm x 0,000 mm	0,000 g (61,000 g)	0,000 Cubic dec.
4008321963857	Shipping carton box contains 10 Piece	71,000 mm x 114,000 mm x 271,000 mm	0,687 kg (0,610 kg)	2,193 Cubic dec.



product details

MR16 20 D

This attractive LED lamp with its GU5.3 base will fit wherever a 20 W low-voltage halogen reflector lamp with the same base is normally used.

- Professional LED lamp as a 12 V version with GU5.3 base
- Very low energy consumption
- Extremely long life
- Equipped with high-efficiency OSRAM High-Power Golden DRAGON LEDs
- No UV radiation in the light beam
- Shockproof and vibration-proof
- Efficient generation of white light
- Operated with conventional transformers with 12 V AC, 50/60Hz or electronic transformers with 12 V

Application

- As a downlight for marking walkways, doors, stairs, etc.
- For exhibitions, department stores