

LP SERIES-General Purpose

LP12-2.0C1 (12V2.0AH)



Specification

Nominal Voltage	12V	
Nominal Capacity(20HR)	2.0AH	
Dimension	Length	143 ± 1mm (5.63 inches)
	Width	24 ± 1mm (0.94 inches)
	Container Height	65 ± 1mm (2.56 inches)
	Total Height (with Terminal)	65 ± 1mm (2.56 inches)
Approx Weight	Approx 0.57 kg (1.26lbs)	
Terminal	/	
Container Material	ABS	
Rated Capacity	2.00 AH/0.10A	(20hr, 1.80V/cell, 25°C/77°F)
	1.86 AH/0.186A	(10hr, 1.80V/cell, 25°C/77°F)
	1.70 AH/0.34A	(5hr, 1.75V/cell, 25°C/77°F)
	1.53 AH/0.51A	(3hr, 1.75V/cell, 25°C/77°F)
	1.26 AH/1.26A	(1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	30A (5s)	
Internal Resistance	Approx 70mΩ	
Operating Temp. Range	Discharge	-15 ~ 50°C (5 ~ 122°F)
	Charge	0 ~ 40°C (32 ~ 104°F)
	Storage	-15 ~ 40°C (5 ~ 104°F)
Nominal Operating Temp. Range	25 ± 3°C (77 ± 5°F)	
Cycle Use	Initial Charging Current less than 0.6A. Voltage	
	14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage	
	13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	Leoch LP series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	

Applications

- ◆ All purpose
- ◆ Uninterruptable Power Supply (UPS)
- ◆ Electric Power System (EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and security system
- ◆ Electronic apparatus and equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto control system



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	3.81	2.92	2.42	2.09	1.62	1.19	1.01	0.59	0.47	0.38	0.309	0.268	0.216	0.180	0.099
1.80V/cell	5.11	3.74	2.93	2.48	1.91	1.39	1.13	0.65	0.50	0.40	0.331	0.287	0.229	0.186	0.100
1.75V/cell	5.76	4.11	3.20	2.66	1.98	1.44	1.18	0.67	0.51	0.41	0.340	0.295	0.233	0.191	0.101
1.70V/cell	6.35	4.48	3.41	2.80	2.07	1.50	1.22	0.69	0.52	0.42	0.349	0.301	0.236	0.195	0.103
1.65V/cell	7.00	4.83	3.63	2.97	2.18	1.54	1.24	0.70	0.55	0.44	0.358	0.308	0.240	0.199	0.104
1.60V/cell	7.72	5.24	3.88	3.17	2.30	1.60	1.26	0.73	0.56	0.45	0.370	0.314	0.242	0.201	0.105


Constant Power Discharge (Watts) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	6.96	5.40	4.52	3.95	3.09	2.29	1.94	1.16	0.91	0.74	0.61	0.53	0.426	0.357	0.196
1.80V/cell	9.25	6.82	5.39	4.60	3.59	2.65	2.16	1.25	0.97	0.79	0.65	0.56	0.451	0.368	0.198
1.75V/cell	10.20	7.38	5.81	4.90	3.69	2.72	2.25	1.29	0.98	0.80	0.66	0.58	0.458	0.377	0.200
1.70V/cell	10.93	7.86	6.12	5.11	3.82	2.82	2.31	1.32	1.01	0.82	0.68	0.59	0.464	0.384	0.203
1.65V/cell	11.88	8.40	6.46	5.39	4.00	2.86	2.35	1.33	1.05	0.85	0.69	0.60	0.470	0.391	0.205
1.60V/cell	12.80	8.91	6.79	5.68	4.19	2.97	2.36	1.39	1.08	0.87	0.71	0.61	0.473	0.395	0.206


Dimensions

Terminal


Unit: mm [inches]




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics



Sales Office

China sales office:

Add: 5th Floor, Xinbaohui Bldg., Nanhai Blvd.,
Nanshan, Shenzhen, China. 518052
Tel: +86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail: export@leoch.com
Http://www.leoch.com

North America sales office:

Add: 19751 Descartes, Unit A,
Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us
Http://www.leoch.us

Europe sales office:

Add: La Campagna House, Main Road,
Gloucester, GL2-8JH, United Kingdom
Tel: +44(0) 1452 751016
E-mail: Sales.Europe@leoch.com
Http://www.leoch.com