LEOCH
理士電池 ®
Leoch Battery

LPS SERIES-Solar Power

LPS2-350 (2V345AH)

Specification

Nomial Voltage	2V
Nomial Capacity(100HR)	350.0AH
Dimension	Length 170±2mm (6.69 inches) Width 150±2mm (5.91 inches) Container Height 328±2mm (12.91 inches) Total Height (with Terminal) 350±2mm (13.78 inches)
Approx Weight	Approx 20.2 Kg(44.5 lbs)
Terminal	T11
Container Material	ABS
Rated Capacity	345.0 AH/3.45A (100hr ,1.80V/cell,25°C/77°F) 318.0 AH/15.9A (20hr ,1.80V/cell,25°C/77°F) 300.0 AH/30.0A (10hr,1.80V/cell,25°C/77°F) 71.0 AH/51.8A (5hr,1.75V/cell,25°C/77°F) 48.3 AH/181.5A (1hr,1.60V/cell,25°C/77°F)
Max. Discharge Current	2400A (5s)
Internal Resistance	Approx 0.9mΩ
Operating Temp.Range	Discharge : -15～50°C (5～122°F) Charge : 0～40°C (32～104°F) Storage : -15～40°C (5～104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)
Cycle Use	Initial Charging Current less than90.0A.Voltage 2.4V~2.5V at 25°C(77°F)Temp. Coefficient -5mV/°C
Standby Use	No limit on Initial Charging Current Voltage 2.25V~2.3V at 25°C(77°F)Temp. Coefficient -3mV/°C
Capacity affected by Temperature	40°C (104°F) 103% 25°C (77°F) 100% 0°C (32°F) 86%
Self Discharge	Leoch LPS series batterys may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.

Applications

- Green energy systems
- Communication systems

Leoch battery is green battery, focus on the Environmental protection and Ecological protection, which well connect human being and environment into harmony. Continous power supply for people, and being benign cycle back to the green environment.

VdS Intertek ETL SEMKO MH26866
ISO14001 ISO9001 CE EMC tested

Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	15min	20min	30min	45min	1h	2h	3h	4h	5h	8h	10h	20h	48h	100h
1.85V/cell	283.1	250.9	208.9	165.2	138.2	91.0	69.0	56.0	47.6	33.7	28.9	15.4	6.92	3.39
1.80V/cell	320.2	279.3	228.1	178.0	146.5	96.8	72.8	58.8	50.0	35.4	30.0	15.9	7.04	3.45
1.75V/cell	361.5	309.0	248.0	192.0	158.7	101.6	76.5	61.4	51.8	36.4	30.7	16.2	7.16	3.52
1.70V/cell	400.4	340.5	270.2	202.4	168.0	107.2	80.2	64.1	54.0	37.8	31.7	16.6	7.26	3.56
1.65V/cell	427.4	361.1	284.1	216.0	174.1	110.9	83.1	66.3	55.9	38.8	32.4	17.0	7.38	3.60
1.60V/cell	474.0	397.2	306.8	225.2	181.5	115.1	85.9	68.4	57.9	39.8	33.2	17.4	7.51	3.64

Constant Power Discharge (Watts) at 25 °C (77°F)

F.V/Time	15min	20min	30min	45min	1h	2h	3h	4h	5h	8h	10h	20h	48h	100h
1.85V/cell	530.9	475.3	400.0	319.1	267.8	177.5	135.0	110.1	93.7	66.7	57.3	30.6	13.8	6.77
1.80V/cell	592.3	521.2	430.2	341.1	282.4	187.6	141.8	114.8	97.9	69.9	59.5	31.6	14.0	6.87
1.75V/cell	660.7	571.2	463.9	364.4	304.5	196.2	148.4	119.6	101.1	71.8	60.8	32.2	14.2	7.00
1.70V/cell	721.5	624.7	502.5	382.7	321.3	206.5	155.3	124.5	105.3	74.3	62.6	32.9	14.4	7.08
1.65V/cell	764.3	657.6	524.2	404.8	330.7	212.5	160.2	128.3	108.6	76.1	63.9	33.6	14.6	7.15
1.60V/cell	833.7	715.6	562.1	419.8	342.9	219.3	164.8	132.0	112.1	78.0	65.5	34.3	14.9	7.21

Dimensions

T11 Terminal

Unit: mm [inches]









Discharge Characteristics



Effect of Temperature on Long Term Float Life



Cycle Service Life



Self-Discharge at Different Temperatures





Charge Mode

A With switch regulator (two-step controller) chargeon curve max.charge voltage for max.2 hrs/day then switch over to continouscharge

B Standard charge without switching

C Boost charge (Equalizing charge with externalgenerator) charge on curve continous charge for max. 5 hrs/month, thenswitch over to curve Standard charge

Sales Office

China sales office:

Add:5th Floor,Xinbaohui Bldg.,Nanhai Blvd.,
Nanshan,Shenzhen, China. 518052
Tel:+ 86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail:export@leoch.com
Http://www.leoch.com

North America sales office:

Add: 19751 Descartes, Unit A,
Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us
Http://www.leoch.us

Europe sales office:

Add: LaCampagna House. Main Road.
Gloucester. GL2-8JH. United Kingdom
Tel: +44(0) 1452 751016
E-mail:Sales.Europe@leoch.com
Http://www.leoch.com