



FEATURES

-Hour meter

Lets users know the timing when to replace the consumables such as oil and spark plug.

-Circuit protector equipped for each of the 3 outlets

Keeps the electric devices that are connected to the other 2 operated when 1 of the 3 shutdowns.

-Oil Alert & Auto shutdown

Stops the engine automatically when it lacks enough oil.

-4-Wheel portability is standard

Models			SH13000		SHT15000
Type			R	LD	R
Generator	Frequency (Hz)		50	60	50
	Type		2-pole, Field Rotating Type		
	Voltage Regulation System		AVR		
	Phase		Single		Three
	AC Output	Rated Power (KVA)	50Hz	10.0	-
60Hz			-	11.8	-
Maximum		50Hz	11.0	-	13.2

	Power (KVA)	60Hz	-	13.0	-
	Rated Voltage (V)	220	120/240	220/380	
	Rated Ampere (A)	45.5	49.2 x 2 / 49.2	18.2	
	Rated Power Factor (cosφ)	1.0		0.8	
Engine	Maker	ROBIN			
	Model	EH72 - 2DS			
	Type	Air-Cooled, 4-Stroke, V-Twin Cylinder Horizontal P.T.O. Shaft, OHV Gasoline Engine			
	Displacement (CC)	720			
	Maximum Output (PS)	Gross: 25.4 (at 3,600rpm)			
	Ignition System	Flywheel magnet (solid state)			
	Starting System	Electric Starter			
	Engine Oil Refill Capacity (ℓ)	1.55 (inclusive of oil filter's capacity)			
	Lubrication System	Full Pressure with Trochoid pump, Oil cooler and Spin-on, full-flow oil filter			
	Cooling System	Forced Air			
Others	L X W X H (mm)	924 x 665 x 636 (804 with wheels)			
	Dry Weight (kg)	without wheel	175		
		with wheel	183		
	Fuel Tank Capacity (liters)	38			
	Sound Level [dB(A)/7m]	50Hz	76	-	76
		60Hz	-	78	-
	Continuous Operating Hours (hr)	50Hz	5.5	-	5.5
		60Hz	-	4.5	-
	Oil Alert & Auto Shutdown System	Equipped			
	4-wheel kit	Equipped			



Robin Machineries & Equipment

Tel: 000971-4-2217124

Fax: 000971-4-2234493

POBox: 5229 Dubai, UAE

Email: alawitra@emirates.net.ae

www.alawigroup.ae