

GENERATING SET GE 3200 H FAMILY



- Honda OHC petrol engine
- Engine shut down for low oil level
- Single-Phase synchronous alternator
- Output sockets: 2 x 230V 16A 2P+T SCHUKO
- Overload thermal shut off
- Battery charger with fuse protection
- Protective frame
- Portable
- Meets EC directives

Standard Equipment										
	Petrol engine	Air cooling	Manual recoil	Engine shut down (oil)						
	Synchronous alternator	Sockets	Thermal shut off	Battery charger						

Options on request

- 230V Plug

- Earthing kit

Technical data

GE 3200 H FAMILY

A.C. GENERATION - 50 Hz

Single-phase synchronous alternator, self-excited, self-regulated, brushless

* Stand-by single-phase power	2.8 kVA / 230V / 12.2A
* P.R.P. single-phase power	2.4 kVA / 230V / 10.4A
Cosφ	1
Battery charger	12Vd.c - 10A
Insulation class	H

* Output powers according to ISO 8528-1

ENGINE

4-stroke petrol, air cooled, OHC

Model	Honda GC 190
* Stand-By net power	3.5 kW (4.8 HP)
* P.R.P. net power	2.7 kW (3.7 HP)
Cylinders/ Displacement	1/ 187 cm ³
Speed	3000 rpm
Fuel consumption (75% of P.R.P.)	1.05 l/h

* Powers according to SAE J1349

GENERAL SPECIFICATIONS

Tank capacity	1.8 l
Running time (75% of P.R.P.)	1.7 h
IP protection degree	IP 23
Dimensions LxWxh (mm)	555x370x390 mm
Dry weight	35 kg
*Acoustic power L _{WA} (pressure L _{PA})	98 dB(A) (73 dB(A) @ 7m)

* For indoor use / For fixed installation only, in compliance with Directive 2000/14/CE