

GENERATING SET GE 7500 BS/GS

- Honda OHV petrol engine
- Engine shut down for low oil level
- Three-Phase synchronous alternator
- Output sockets : 1 x 400V 16A 3P+N+T CEE
1 x 230V 16A 2P+T CEE
- ELCB-GFI (ground fault interruptor)
- Circuit breaker
- Wrap around protective frame
- Meets EC directives



| | | | | | | | | | | |
|--------------------|--|-------------|--|------------------------|---|-----------------|-----------|--------------------|---|--|
| Standard Equipment | | | | | | | | | | |
| | Petrol engine | Air cooling | Manual recoil | Engine shut down (oil) | Hour-meter | | | | | |
| | | | | | | | | | | |
| | Synchronous alternator | Compound | Sockets 3~ | Sockets 1~ | ELCB-GFI | Circuit Breaker | Voltmeter | | | |
| Options on request | <ul style="list-style-type: none"> ● 400V plug ● 230V plug | | <ul style="list-style-type: none"> ● Earthing kit | | <ul style="list-style-type: none"> ● Exhaust extension ● Trolley CTM200 | | | Version on request | <ul style="list-style-type: none"> ● Schuko socket | |

Technical Data

GE 7500 BS/GS

A.C GENERATION – 50 Hz

Three-phase synchronous alternator, self-excited, self-regulated

* Stand-by three-phase power
* P.R.P. three-phase power
* P.R.P. single-phase power
Cosφ
Insulation class

7.5 kVA (6 kW) / 400 V / 10.8 A
6.5 kVA (5.2 kW) / 400 V / 9.4 A
4 kVA / 230 V / 17.4 A
0.8
H

* Output powers according to ISO 8528-1

ENGINE

4-stroke petrol, air cooled, OHV

Model
* Stand-By net power
* P.R.P. net power
Cylinders/ Displacement
Speed
Fuel consumption (75% of P.R.P.)

Honda GX 390
7.7 kW (10.5 HP)
6 kW (8.1 HP)
1/ 389 cm³
3000 rpm
2.5 l/h

* Powers according to SAE J1349

GENERAL SPECIFICATION

Tank capacity
Running time (75% of P.R.P.)
IP protection degree
*Dimensions LxWxh (mm)
*Dry weight
**Measured acoustic power LwA (pressure LpA)
**Guaranteed acoustic power LwA (pressure LpA)

6.1 l
2.5 h
IP 23
910x525x613 mm
87 kg
96 dB(A)(71 dB(A) @ 7m)
97 dB(A)(72 dB(A) @ 7m)

* Dimensions and weight without trolley/trailer. ** Acoustic power according to European Directive 2000/14/EC

Mosa reserves the right to change this specification without notice. For further information please contact the sales department